

Amendments to the Claims

This listing of claims will replace all prior versions and listings of claims in the above-identified application.

Listing of Claims

1. (Currently amended) A method ~~for restoring a virtual path in an optical network, the method~~ comprising:
 - identifying a plurality of nodes with resources, wherein said nodes with resources are comprised in an optical network and have ones of said nodes having a resource necessary to support a [[said]] virtual path, wherein said identifying said plurality of nodes with resources comprises determining whether a candidate node has sufficient resources to support said virtual path, and said determining is performed by said candidate node; and
 - identifying an alternate physical path using a result of said identifying said plurality of nodes with resources, said alternate physical path comprising ones of said nodes with resources.
2. (Original) The method of claim 1, further comprising:
 - restoring said virtual path using said alternate physical path.
3. (Original) The method of claim 2, wherein said restoring is done by
 - configuring said alternate physical path by establishing a communication connection between said ones of said nodes with resources; and
 - provisioning said virtual path over said alternate physical path.

4. **(Currently amended)** The method of claim 2, further comprising:
detecting a failure in said virtual path; wherein
said detection of said failure is done by receiving a failure message packet;
said virtual path is provisioned on a physical path between a first and a second node of
said optical network;
said optical network comprises ~~said nodes~~, and said nodes comprise said nodes with
resources;
each one of said nodes is coupled to at least one other of said nodes by a plurality of
optical links;
said physical path between said first and said second node comprises a plurality of
intermediate nodes; and
each one of said nodes is coupled to at least one other of said nodes in a mesh topology.
5. **(Original)** The method of claim 4, wherein said restoring of said virtual path is
completed in less than 2 seconds.
6. **(Original)** The method of claim 4, wherein said restoring of said virtual path is
completed in less than 250 milliseconds.
7. **(Original)** The method of claim 4, wherein said first node receives said failure message
packet.
8. **(Previously presented)** The method of claim 7, further comprising:
 - (i) changing a state of said virtual path to restoring;
 - (ii) identifying an adjacent node with required bandwidth for said virtual path;
 - (iii) forwarding a resource request packet to said adjacent node with required
bandwidth for said virtual path;
 - (iv) waiting for a resource response packet for a predetermined time interval; and
if said resource response packet is not received within said predetermined time interval,
repeating steps (ii) – (iv) for a predefined threshold time.

9. (Original) The method of claim 8, further comprising:
if said resource response packet is not received within said predefined threshold time,
generating a network alarm.
10. (Original) The method of claim 8, further comprising:
if said resource response packet is received with at least one error,
waiting until responses to all resource request packets are received; and
if said resource response packet is received with no errors,
determining if a list of allocated ports in said resource response packet is valid.
11. (Original) The method of claim 10, further comprising:
if said list of allocated port is valid,
provisioning said virtual path on said allocated ports; and
if said list of allocated ports is invalid,
generating a network alarm.
12. (Original) The method of claim 10, further comprising:
if responses to all resource request packets are received with at least one error,
generating a network alarm.
13. (Previously presented) The method of claim 9, wherein said predetermined time interval and predefined threshold time are dynamically calculated by said network.
14. (Original) The method of claim 4, wherein one of said intermediate nodes receives said failure message.

15. (Original) The method of claim 14, further comprising:
changing a state of said virtual path to down;
forwarding said failure message to adjacent nodes comprising said virtual path;
initiating a timer for receiving a response to said forwarded failure message;
if said timer expires before said response to said forwarded failure message is received,
releasing resources of said virtual path; and
if said response to said forwarded failure message is received before said timer expires,
stopping said timer, and
releasing resources of said virtual path.
16. (Original) The method of claim 4, wherein said second node receives said failure message.
17. (Original) The method of claim 16, further comprising:
acknowledging said failure message;
changing a state of said virtual path to down; and
releasing resources of said virtual path.
18. (Previously presented) The method of claim 8, wherein one of said intermediate nodes receives said resource request packet.

19. (Original) The method of claim 18, further comprising:
if said resource request packet includes at least one error,
 copying said resource request packet to a first resource response packet,
 decrementing a hop count field in said first resource response packet,
 adding an error code to said first resource response packet, and
 responding with said first resource response packet; and
if said resource request packet includes no errors,
 allocating a resource to said virtual path,
 incrementing a hop count field in said resource request packet,
 forwarding said resource request packet to an adjacent node having a resource
 necessary to support said virtual path, and
 waiting for a second resource response packet from said adjacent node.
20. (Previously presented) The method of claim 19, further comprising:
if said second resource response packet is not received within a second predetermined
 time interval,
 releasing said resource allocated to said virtual path, and
 forwarding a negative acknowledgment to said first node.
21. (Previously presented) The method of claim 19, further comprising:
if said second resource response packet is received with at least one error,
 releasing said resource allocated to said virtual path,
 decrementing a hop count field in said second resource response packet, and
 forwarding said second resource response packet to said first node; and
if said second resource response packet is received with no errors,
 determining if said second resource response packet includes a valid list of a
 plurality of ports.

22. (Original) The method of claim 21, further comprising:
if said list of said plurality of ports is invalid,
 releasing resources allocated to said virtual path, and
 forwarding a negative acknowledgement to said first node;
if said list of said plurality of ports is valid,
 determining if said plurality of ports is available;
if said plurality of ports is available,
 assigning said plurality of ports to said virtual path, and
 updating said virtual path information in a node database;
if said plurality of ports is not available,
 adding an error code to said second resource response packet;
decrementing a hop count field in said second resource response packet; and
forwarding said second resource response packet to said first node.
23. (Original) The method of claim 18, further comprising:
if a state of said virtual path is one of 'restoring' and 'deleting',
 copying said resource request packet to said first resource response packet,
 decrementing said hop count field in said first resource response packet,
 adding an error code of to said first resource response packet, and
 responding with said first resource response packet.
24. (Original) The method of claim 8, wherein said second node receives said resource request packet.
25. (Original) The method of claim 24, further comprising:
if said resource request packet includes invalid information,
 copying said resource request packet to a third resource response packet,
 decrementing a hop count field in said third resource response packet,
 adding an error code to said third resource response packet, and
 responding with said third resource response packet; and
if said resource request packet includes valid information,
 determining if a resource is available for said virtual path.

26. (Original) The method of claim 25, further comprising:
if said resource is available for said virtual path,
 copying said resource request packet to said third resource response packet,
 allocating said resource to said virtual path,
 updating said virtual path information in a node database,
 decrementing a hop count field in said third resource response packet,
 adding a list of a plurality of ports to said third resource response packet, and
 responding with said third resource response packet.
27. (Original) The method of claim 25, further comprising:
if said resource is not available for said virtual path,
 copying said resource request packet to said third resource response packet,
 decrementing said hop count field in said third resource response packet,
 adding an error code to said third resource response packet, and
 responding with said third resource response packet.
28. (Original) The method of claim 24, further comprising:
if a state of said virtual path is one of 'restoring' and 'deleting',
 copying said resource request packet to said third resource response packet,
 decrementing said hop count field in said third resource response packet,
 adding an error code to said third resource response packet, and
 responding with said third resource response packet.

29. **(Currently amended)** A network element ~~configured to restore a virtual path in an optical network, the network element~~ comprising:

a processor configured to restore a virtual path in an optical network;

a memory coupled to said processor; and

a network interface coupled to said processor; said processor configured to

identify a plurality of nodes with resources, wherein said nodes with resources are

comprised in said optical network and have ones of said nodes having a

resource necessary to support said virtual path, wherein to identify said

plurality of nodes with resources said processor is configured to determine

whether a candidate node comprising said network element has sufficient

resources to support said virtual path, and

identify an alternate physical path using a result of said identifying said plurality

of nodes with resources, said alternate physical path comprising ones of

said nodes with resources.

30. **(Original)** The network element of claim 29, wherein said processor is further configured to

restore said virtual path using said alternate physical path.

31. **(Original)** The network element of claim 29, wherein said processor is further configured to

configure said alternate physical path by establishing a communication connection

between said ones of said nodes with resources; and

provision said virtual path over said alternate physical path.

32. **(Currently amended)** The network element of claim 29, wherein said processor is further configured to
- detect a failure in said virtual path; wherein
 - said detection of said failure is done by receiving a failure message packet;
 - said virtual path is provisioned on a physical path between a first and a second node of said optical network;
 - said optical network comprises ~~said nodes~~, and said nodes comprise said nodes with resources;
 - each one of said nodes is coupled to at least one other of said nodes by a plurality of optical links;
 - said physical path between said first and said second node comprises a plurality of intermediate nodes; and
 - each one of said nodes is coupled to at least one other of said nodes in a mesh topology.
33. **(Original)** The network element of claim 32, wherein said processor is further configured to restore said virtual path in less than 2 seconds.
34. **(Original)** The network element of claim 32, wherein said processor is further configured to restore said virtual path in less than 250 milliseconds.
35. **(Previously presented)** The network element of claim 32, wherein
- said network element is configured as said first node; and
 - said network element is configured to receive said failure message packet.

36. **(Currently amended)** The network element of claim 35, wherein said processor is further configured to

- (i) change a state of said virtual path to restoring;
 - (ii) identify an adjacent node with required bandwidth for said virtual path;
 - (iii) forward a resource request packet to said adjacent node with required bandwidth for said virtual path;
 - (iv) wait for a resource response packet for a predetermined time interval; **and**
 - (v) if said resource response packet is not received within said predetermined time interval, repeat steps (ii) – (iv) for a predefined threshold time. [[; and]]
- ~~repeat steps (ii) – (iv) for a predefined threshold time.~~

37. **(Original)** The network element of claim 36, wherein said processor is further configured to

if said resource response packet is not received within said predefined threshold time,
generate a network alarm.

38. **(Original)** The network element of claim 36, wherein said processor is further configured to

if said resource response packet is received with at least one error,
wait until responses to all resource request packets are received; and
if said resource response packet is received with no errors,
determine if a list of allocated ports in said resource response packet is valid.

39. **(Original)** The network element of claim 38, wherein said processor is further configured to

if said list of allocated port is valid,
provision said virtual path on said allocated ports; and
if said list of allocated ports is invalid,
generate a network alarm.

40. (Original) The network element of claim 38, wherein said processor is further configured to
if responses to all resource request packets are received with at least one error,
generate a network alarm.
41. (Previously presented) The network element of claim 39, wherein said predetermined time interval and predefined threshold time are dynamically calculated by said network.
42. (Previously presented) The network element of claim 32, wherein
said network element is configured as one of said intermediate nodes, and
said network element is configured to receive said failure message packet.
43. (Original) The network element of claim 42, wherein said processor is further configured to
change a state of said virtual path to down;
forward said failure message to adjacent nodes comprising said virtual path;
initiate a timer for receiving a response to said forwarded failure message;
if said timer expires before said response to said forwarded failure message is received,
release resources of said virtual path; and
if said response to said forwarded failure message is received before said timer expires,
stop said timer, and
release resources of said virtual path.
44. (Previously presented) The network element of claim 32, wherein
said network element is configured as said second node, and
said network element receives said failure message.
45. (Original) The network element of claim 44, wherein said processor is further configured to
acknowledge said failure message;
change a state of said virtual path to down; and
release resources of said virtual path.

46. (Original) The network element of claim 36, wherein
said network element is configured as one of said intermediate nodes, and
said network element receives said resource request packet.
47. (Original) The network element of claim 46, wherein said processor is further configured
to
if said resource request packet includes at least one error,
 copy said resource request packet to a first resource response packet,
 decrement a hop count field in said first resource response packet,
 add an error code to said first resource response packet, and
 respond with said first resource response packet; and
if said resource request packet includes no errors,
 allocate a resource to said virtual path,
 increment a hop count field in said resource request packet,
 forward said resource request packet to an adjacent node having a resource
 necessary to support said virtual path, and
 wait for a second resource response packet from said adjacent node.
48. (Previously presented) The network element of claim 47, wherein said processor is
further configured to
if said second resource response packet is not received within a second predetermined
time interval,
 release said resource allocated to said virtual path, and
 forward a negative acknowledgment to said first node.

49. (Original) The network element of claim 47, wherein said processor is further configured to
- if said second resource response packet is received with at least one error,
 - release said resources allocated to said virtual path,
 - decrement a hop count field in said second resource response packet, and
 - forward said second resource response packet to said first node; and
 - if said second resource response packet is received with no errors,
 - determine if said second resource response packet includes a valid list of a plurality of ports.
50. (Original) The network element of claim 49, wherein said processor is further configured to
- if said list of said plurality of ports is invalid,
 - release resources allocated to said virtual path, and
 - forward a negative acknowledgement to said first node;
 - if said list of said plurality of ports is valid,
 - determine if said plurality of ports is available;
 - if said plurality of ports is available,
 - assign said plurality of ports to said virtual path, and
 - update said virtual path information in a node database;
 - if said plurality of ports is not available,
 - add an error code to said second resource response packet;
 - decrement a hop count field in said second resource response packet; and
 - forward said second resource response packet to said first node.
51. (Original) The network element of claim 46, wherein said processor is further configured to
- if a state of said virtual path is one of 'restoring' and 'deleting',
 - copy said resource request packet to said first resource response packet,
 - decrement said hop count field in said first resource response packet,
 - add an error code of to said first resource response packet, and
 - respond with said first resource response packet.

52. (Previously presented) The network element of claim 36, wherein said network element is configured as said second node, and said network element is configured to receive said resource request packet.
53. (Original) The network element of claim 52, wherein said processor is further configured to
if said resource request packet includes invalid information,
 copy said resource request packet to a third resource response packet,
 decrement a hop count field in said third resource response packet,
 add an error code to said third resource response packet, and
 respond with said third resource response packet; and
if said resource request packet includes valid information,
 determine if a resource is available for said virtual path.
54. (Original) The network element of claim 53, wherein said processor is further configured to
if said resource is available for said virtual path,
 copy said resource request packet to said third resource response packet,
 allocate said resource to said virtual path,
 update said virtual path information in a node database,
 decrement a hop count field in said third resource response packet,
 add a list of a plurality of ports to said third resource response packet, and
 respond with said third resource response packet.
55. (Original) The network element of claim 53, wherein said processor is further configured to
if said resource is not available for said virtual path,
 copy said resource request packet to said third resource response packet,
 decrement said hop count field in said third resource response packet,
 add an error code to said third resource response packet, and
 respond with said third resource response packet.

56. (Original) The network element of claim 52, wherein said processor is further configured to

if a state of said virtual path is one of 'restoring' and 'deleting',
 copy said resource request packet to said third resource response packet,
 decrement said hop count field in said third resource response packet,
 add an error code to said third resource response packet, and
 respond with said third resource response packet.

57. (Currently amended) A computer system ~~for restoring a virtual path in an optical network, said computer system~~ comprising:

means for identifying a plurality of nodes with resources, wherein said nodes with resources are comprised in an optical network and have ones of said nodes having a resource necessary to support a [[said]] virtual path, said means for identifying said plurality of nodes with resources comprising:
means for determining whether a candidate node has sufficient resources to support said virtual path, and said means for determining is comprised in said candidate node; and
 means for identifying an alternate physical path using a result of said identifying said plurality of nodes with resources, said alternate physical path comprising ones of said nodes with resources.

58. (Original) The computer system of claim 57, further comprising:
 means for restoring said virtual path using said alternate physical path.

59. (Previously presented) The computer system of claim 57, wherein said means for restoring comprises:
 means for configuring said alternate physical path by establishing a communication connection between said ones of said nodes with resources; and
 means for provisioning said virtual path over said alternate physical path.

60. **(Currently amended)** The computer system of claim 58, further comprising:
means for detecting a failure in said virtual path; wherein
said detection of said failure is done by receiving a failure message packet;
said virtual path is provisioned on a physical path between a first and a second node of
said optical network;
said optical network comprises ~~said nodes~~, and said nodes comprise said nodes with
resources;
each one of said nodes is coupled to at least one other of said nodes by a plurality of
optical links;
said physical path between said first and said second node comprises a plurality of
intermediate nodes; and
each one of said nodes is coupled to at least one other of said nodes in a mesh topology.
61. **(Original)** The computer system of claim 60, wherein said restoring of said virtual path is
completed in less than 2 seconds.
62. **(Original)** The computer system of claim 60, wherein said restoring of said virtual path is
completed in less than 250 milliseconds.
63. **(Original)** The computer system of claim 60, wherein said first node receives said failure
message packet.

64. (Previously presented) The computer system of claim 63, further comprising:
- (i) means for changing a state of said virtual path to restoring;
 - (ii) means for identifying an adjacent node with required bandwidth for said virtual path;
 - (iii) means for forwarding a resource request packet to said adjacent node with required bandwidth for said virtual path;
 - (iv) means for waiting for a resource response packet for a predetermined time interval; and
- means for repeating actions of said means (ii) – (iv) for a predefined threshold time if said resource response packet is not received within said predetermined time interval.
65. (Original) The computer system of claim 64, further comprising:
- means for generating a network alarm if said resource response packet is not received within said predefined threshold time.
66. (Original) The computer system of claim 64, further comprising:
- means for waiting until responses to all resource request packets are received if said resource response packet is received with at least one error; and
- means for determining if a list of allocated ports in said resource response packet is valid if said resource response packet is received with no errors.
67. (Original) The computer system of claim 66, further comprising:
- means for provisioning said virtual path on said allocated ports if said list of allocated port is valid; and
- means for generating a network alarm if said list of allocated ports is invalid.
68. (Original) The computer system of claim 66, further comprising:
- means for generating a network alarm if responses to all resource request packets are received with at least one error.

69. (Previously presented) The computer system of claim 65, wherein said predetermined time interval and predefined threshold time are dynamically calculated by said network.
70. (Original) The computer system of claim 60, wherein one of said intermediate nodes receives said failure message.
71. (Original) The computer system of claim 70, further comprising:
means for changing a state of said virtual path to down;
means for forwarding said failure message to adjacent nodes comprising said virtual path;
means for initiating a timer for receiving a response to said forwarded failure message;
means for releasing resources of said virtual path if said timer expires before said
response to said forwarded failure message is received;
means for stopping said timer if said response to said forwarded failure message is
received before said timer expires; and
means for releasing resources of said virtual path if said response to said forwarded
failure message is received before said timer expires.
72. (Original) The computer system of claim 60, wherein said second node receives said failure message.
73. (Original) The computer system of claim 72, further comprising:
means for acknowledging said failure message;
means for changing a state of said virtual path to down; and
means for releasing resources of said virtual path.
74. (Original) The computer system of claim 64, wherein one of said intermediate nodes receives said resource request packet.

75. (Original) The computer system of claim 74, further comprising:
- means for copying said resource request packet to a first resource response packet if said resource request packet includes at least one error;
 - means for decrementing a hop count field in said first resource response packet if said resource request packet includes at least one error;
 - means for adding an error code to said first resource response packet if said resource request packet includes at least one error;
 - means for responding with said first resource response packet if said resource request packet includes at least one error;
 - means for allocating a resource to said virtual path if said resource request packet includes no errors;
 - means for incrementing a hop count field in said resource request packet if said resource request packet includes no errors;
 - means for forwarding said resource request packet to an adjacent node having a resource necessary to support said virtual path if said resource request packet includes no errors; and
 - means for waiting for a second resource response packet from said adjacent node if said resource request packet includes no errors.
76. (Previously presented) The computer system of claim 75, further comprising:
- means for releasing said resource allocated to said virtual path if said second resource response packet is not received within a second predetermined time interval; and
 - means for forwarding a negative acknowledgment to said first node if said second resource response packet is not received within said second predetermined time interval.

77. (Original) The computer system of claim 75, further comprising:
means for releasing said resources allocated to said virtual path if said second resource response packet is received with at least one error;
means for decrementing a hop count field in said second resource response packet if said second resource response packet is received with at least one error;
means for forwarding said second resource response packet to said first node if said second resource response packet is received with at least one error; and
means for determining if said second resource response packet includes a valid list of a plurality of ports if said second resource response packet is received with no errors.
78. (Original) The computer system of claim 77, further comprising:
means for releasing resources allocated to said virtual path if said list of said plurality of ports is invalid;
means for forwarding a negative acknowledgement to said first node if said list of said plurality of ports is invalid;
means for determining if said plurality of ports is available if said list of said plurality of ports is valid;
means for assigning said plurality of ports to said virtual path if said plurality of ports is available;
means for updating said virtual path information in a node database if said plurality of ports is available;
means for adding an error code to said second resource response packet if said plurality of ports is not available;
means for decrementing a hop count field in said second resource response packet; and
means for forwarding said second resource response packet to said first node.

79. (Original) The computer system of claim 74, further comprising:
means for copying said resource request packet to said first resource response packet if a state of said virtual path is one of 'restoring' and 'deleting';
means for decrementing said hop count field in said first resource response packet if a state of said virtual path is one of 'restoring' and 'deleting';
means for adding an error code of to said first resource response packet if a state of said virtual path is one of 'restoring' and 'deleting'; and
means for responding with said first resource response packet if a state of said virtual path is one of 'restoring' and 'deleting'.
80. (Original) The computer system of claim 64, wherein said second node receives said resource request packet.
81. (Original) The computer system of claim 80, further comprising:
means for copying said resource request packet to a third resource response packet if said resource request packet includes invalid information;
means for decrementing a hop count field in said third resource response packet if said resource request packet includes invalid information;
means for adding an error code to said third resource response packet if said resource request packet includes invalid information;
means for responding with said third resource response packet if said resource request packet includes invalid information; and
means for determining if a resource is available for said virtual path if said resource request packet includes valid information.

82. (Original) The computer system of claim 81, further comprising:
means for copying said resource request packet to said third resource response packet if
said resource is available for said virtual path;
means for allocating said resource to said virtual path if said resource is available for said
virtual path;
means for updating said virtual path information in a node database if said resource is
available for said virtual path;
means for decrementing a hop count field in said third resource response packet if said
resource is available for said virtual path;
means for adding a list of a plurality of ports to said third resource response packet if said
resource is available for said virtual path; and
means for responding with said third resource response packet.
83. (Original) The computer system of claim 81, further comprising:
means for copying said resource request packet to said third resource response packet if
said resource is not available for said virtual path;
means for decrementing said hop count field in said third resource response packet if said
resource is not available for said virtual path;
means for adding an error code to said third resource response packet if said resource is
not available for said virtual path; and
means for responding with said third resource response packet.
84. (Original) The computer system of claim 80, further comprising:
means for copying said resource request packet to said third resource response packet if a
state of said virtual path is one of 'restoring' and 'deleting';
means for decrementing said hop count field in said third resource response packet if a
state of said virtual path is one of 'restoring' and 'deleting';
means for adding an error code to said third resource response packet if a state of said
virtual path is one of 'restoring' and 'deleting'; and
means for responding with said third resource response packet.

85. **(Currently amended)** A computer program product ~~for restoring a virtual path in an optical network~~, encoded in computer readable media, said program product comprising a set of instructions executable on a computer system, said set of instructions configured to
- identify a plurality of nodes with resources, wherein said nodes with resources are comprised in an optical network and have ones of said nodes having a resource necessary to support a [[said]] virtual path, wherein to identify said plurality of nodes with resources said instructions are configured to determine whether a candidate node comprising said computer system has sufficient resources to support said virtual path; and
- identify[[ing]] an alternate physical path using a result of said identifying said plurality of nodes with resources, said alternate physical path comprising ones of said nodes with resources.
86. **(Original)** The computer program product of claim 85, wherein said set of instructions is further configured to
- restore said virtual path using said alternate physical path.
87. **(Original)** The computer program product of claim 85, wherein said set of instructions is further configured to
- configure said alternate physical path by establishing a communication connection between said ones of said nodes with resources; and
- provision said virtual path over said alternate physical path.

88. **(Currently amended)** The computer program product of claim 85, wherein said set of instructions is further configured to

detect a failure in said virtual path; wherein

said detection of said failure is done by receiving a failure message packet;

said virtual path is provisioned on a physical path between a first and a second node of
said optical network;

said optical network comprises ~~said nodes~~, and said nodes comprise said nodes with
resources;

each one of said nodes is coupled to at least one other of said nodes by a plurality of
optical links;

said physical path between said first and said second node comprises a plurality of
intermediate nodes; and

each one of said nodes is coupled to at least one other of said nodes in a mesh topology.

89. **(Original)** The computer program product of claim 88, wherein said set of instructions is further configured to restore said virtual path in less than 2 seconds.

90. **(Original)** The computer program product of claim 88, wherein said set of instructions is further configured to restore said virtual path in less than 250 milliseconds.

91. **(Previously presented)** The computer program product of claim 88, wherein said first node receives said failure message packet.

92. **(Currently amended)** The computer program product of claim 91, wherein said set of instructions is further configured to

- (i) change a state of said virtual path to restoring;
- (ii) identify an adjacent node with required bandwidth for said virtual path;
- (iii) forward a resource request packet to said adjacent node with required bandwidth for said virtual path;
- (iv) wait for a resource response packet for a predetermined time interval; **and**
- (v) if said resource response packet is not received within said predetermined time interval, repeat steps (ii) – (iv) for a predefined threshold time. [[; and]]
~~repeat steps (ii) – (iv) for a predefined threshold time.~~

93. **(Original)** The computer program product of claim 92, wherein said set of instructions is further configured to

if said resource response packet is not received within said predefined threshold time,
generate a network alarm.

94. **(Previously presented)** The computer program product of claim 92, wherein said set of instructions is further configured to

if said resource response packet is received with at least one error,
wait until responses to all resource request packets are received; and
if said resource response packet is received with no errors,
determine if a list of allocated ports in said resource response packet is valid.

95. **(Original)** The computer program product of claim 94, wherein said set of instructions is further configured to

if said list of allocated port is valid,
provision said virtual path on said allocated ports; and
if said list of allocated ports is invalid,
generate a network alarm.

96. (Original) The computer program product of claim 93, wherein said set of instructions is further configured to

if responses to all resource request packets are received with at least one error,
generate a network alarm.

97. (Previously presented) The computer program product of claim 92, wherein said predetermined time interval and predefined threshold time are dynamically calculated by said network.

98. (Original) The computer program product of claim 88, wherein one of said intermediate nodes receives said failure message.

99. (Original) The computer program product of claim 88, wherein said set of instructions is further configured to

change a state of said virtual path to down;
forward said failure message to adjacent nodes comprising said virtual path;
initiate a timer for receiving a response to said forwarded failure message;
if said timer expires before said response to said forwarded failure message is received,
release resources of said virtual path; and
if said response to said forwarded failure message is received before said timer expires,
stop said timer, and
release resources of said virtual path.

100. (Original) The computer program product of claim 88, wherein said second node receives said failure message.

101. (Original) The computer program product of claim 100, wherein said set of instructions is further configured to

acknowledge said failure message;
change a state of said virtual path to down; and
release resources of said virtual path.

102. (Original) The computer program product of claim 92, wherein one of said intermediate nodes receives said resource request packet.

103. (Original) The computer program product of claim 92, wherein said set of instructions is further configured to

if said resource request packet includes at least one error,

copy said resource request packet to a first resource response packet,

decrement a hop count field in said first resource response packet,

add an error code to said first resource response packet, and

respond with said first resource response packet; and

if said resource request packet includes no errors,

allocate a resource to said virtual path,

increment a hop count field in said resource request packet,

forward said resource request packet to an adjacent node having a resource

necessary to support said virtual path, and

wait for a second resource response packet from said adjacent node.

104. (Previously presented) The computer program product of claim 103, wherein said set of instructions is further configured to

if said second resource response packet is not received within a second predetermined time interval,

release said resource allocated to said virtual path, and

forward a negative acknowledgment to said first node.

105. (Original) The computer program product of claim 103, wherein said set of instructions is further configured to

- if said second resource response packet is received with at least one error,
 - release said resources allocated to said virtual path,
 - decrement a hop count field in said second resource response packet, and
 - forward said second resource response packet to said first node; and
- if said second resource response packet is received with no errors,
 - determine if said second resource response packet includes a valid list of a plurality of ports.

106. (Original) The computer program product of claim 105, wherein said set of instructions is further configured to

- if said list of said plurality of ports is invalid,
 - release resources allocated to said virtual path, and
 - forward a negative acknowledgement to said first node;
- if said list of said plurality of ports is valid,
 - determine if said plurality of ports is available;
- if said plurality of ports is available,
 - assign said plurality of ports to said virtual path, and
 - update said virtual path information in a node database;
- if said plurality of ports is not available,
 - add an error code to said second resource response packet;
- decrement a hop count field in said second resource response packet; and
- forward said second resource response packet to said first node.

107. (Original) The computer program product of claim 102, wherein said set of instructions is further configured to

- if a state of said virtual path is one of 'restoring' and 'deleting',
 - copy said resource request packet to said first resource response packet,
 - decrement said hop count field in said first resource response packet,
 - add an error code of to said first resource response packet, and
 - respond with said first resource response packet.

108. (Original) The computer program product of claim 92, wherein said second node receives said resource request packet.

109. (Original) The computer program product of claim 108, wherein said set of instructions is further configured to

- if said resource request packet includes invalid information,
 - copy said resource request packet to a third resource response packet,
 - decrement a hop count field in said third resource response packet,
 - add an error code to said third resource response packet, and
 - respond with said third resource response packet; and
- if said resource request packet includes valid information,
 - determine if a resource is available for said virtual path.

110. (Original) The computer program product of claim 109, wherein said set of instructions is further configured to

- if said resource is available for said virtual path,
 - copy said resource request packet to said third resource response packet,
 - allocate said resource to said virtual path,
 - update said virtual path information in a node database,
 - decrement a hop count field in said third resource response packet,
 - add a list of a plurality of ports to said third resource response packet, and
 - respond with said third resource response packet.

111. (Original) The computer program product of claim 108, wherein said set of instructions is further configured to

- if said resource is not available for said virtual path,
 - copy said resource request packet to said third resource response packet,
 - decrement said hop count field in said third resource response packet,
 - add an error code to said third resource response packet, and
 - respond with said third resource response packet.

112. (Previously presented) The computer program product of claim 108, wherein said set of instructions is further configured to

if a state of said virtual path is one of 'restoring' and 'deleting',
 copy said resource request packet to said third resource response packet,
 decrement said hop count field in said third resource response packet,
 add an error code to said third resource response packet, and
 respond with said third resource response packet.

113. **(Currently amended)** A network element configured to restore a virtual path in an optical network, the network element comprising:

a processor;
 a memory coupled to said processor; and
 a network interface coupled to said processor; said processor configured to
 identify a plurality of nodes with resources, wherein said nodes with resources are
comprised in said optical network and have ~~ones of said nodes having~~ a
 resource necessary to support said virtual path,
 identify an alternate physical path, said alternate physical path comprising ones of
 said nodes with resources,
 detect a failure in said virtual path,
 change a state of said virtual path to restoring,
 (i) identify an adjacent node with required bandwidth for said virtual path,
 (ii) forward a resource request packet to said adjacent node with required
 bandwidth for said virtual path,
 (iii) wait for a resource response packet for a predetermined time interval, and
 if said resource response packet is not received within said predetermined time
 interval, repeat steps (i)–(iii) for a predefined threshold time;

wherein,

said detection of said failure is done by receiving a failure message packet;
 said virtual path is provisioned on a physical path between a first and a second node of
 said optical network;
 said optical network comprises ~~said nodes~~, and said nodes comprise said nodes with
resources;

each one of said nodes is coupled to at least one other of said nodes by a plurality of optical links;
said physical path between said first and said second node comprises a plurality of intermediate nodes;
each one of said nodes is coupled to at least one other of said nodes in a mesh topology;
said network element is configured as said first node; and
said network element is configured to receive said failure message packet.

114. **(Currently amended)** The method of claim 1, wherein said identifying ~~[[the]]~~ said plurality of nodes with resources comprises determining whether a node under consideration would be appropriate for use in restoring said virtual path by virtue of having sufficient resources to support a physical path to be used by said virtual path.

115. **(Previously presented)** The method of claim 114, wherein said resources comprise an available bandwidth.

116. **(Previously presented)** The method of claim 114, wherein said resources comprise an available port.

117. **(Previously presented)** The method of claim 114, wherein said resources comprise an available class of service.

118. **(Canceled)**

119. **(Currently amended)** The method of claim 1, wherein said identifying ~~[[the]]~~ said plurality of nodes with resources comprises rejecting a candidate node if ~~[[the]]~~ said candidate node does not have sufficient resources to support said virtual path.